

### Insulation shell for valve C2..Q-..

- only for non-condensing applications
- easy mounting thanks to velcro strip
- can also be mounted/dismounted subsequently



Picture may differ from product

### Type Overview

| Type              | DN | Suitable for | Weight   |
|-------------------|----|--------------|----------|
| EXT-OC-ZR-C215Q   | 15 | C215Q-..     | 0.007 kg |
| EXT-OC-ZR-C220Q-K | 20 | C220Q-..     | 0.010 kg |
| EXT-OC-ZR-C225    | 25 | C225Q-..     | 0.010 kg |

### Technical data

|                        |                      |                                                               |
|------------------------|----------------------|---------------------------------------------------------------|
| <b>Functional data</b> | Thermal conductivity | 0.035 W/mK                                                    |
| <b>Materials</b>       | Used materials       | Polyethylen foam (PE-3015 acc. EN 12667:2001 / EN 12664:2001) |

### Safety notes



- This accessory has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.
- The accessory may not be disposed of as household refuse. All locally valid regulations and requirements must be observed.