


Average temperature sensor

Active sensor (4...20 mA) for measuring the average temperature in duct applications. IP65 / NEMA 4X rated housing. Supplied with one continuous sensing element across the whole length of the probe to ensure optimum accuracy and eliminate air stratification problems.


Type Overview

Type	Output signal active temperature	Probe length
22MT-144	4...20 mA	3 m
22MT-145	4...20 mA	6 m
22MT-148	4...20 mA	15 m

Technical data

Electrical data	Nominal voltage	DC 24 V																																				
	Nominal voltage range	DC 15...35 V																																				
	Power consumption DC	0.5 W																																				
	Electrical connection	Pluggable spring loaded terminal block max. 2.5 mm²																																				
	Cable entry	Cable gland with strain relief ø6...8 mm																																				
Functional data	Medium	Air																																				
	Multirange	8 measuring ranges selectable																																				
	Current output	1x 4...20 mA, max. resistance 500 Ω																																				
Measuring data	Measured values	Temperature																																				
Specification temperature active	Sensing element technology	Based on Pt1000 class AA																																				
	Measuring range temperature settings	Active sensor: range selectable Attention: The maximum measuring range listed does not indicate the allowable fluid temperature for the sensor. Refer to safety data for the maximum fluid temperature limits.																																				
		<table><tr><td>*del*Setting</td><td>Range [°C]</td><td>Range [°F]</td><td>Factory setting</td></tr><tr><td>S0</td><td>-50...50</td><td>-30...130</td><td></td></tr><tr><td>S1</td><td>-10...120</td><td>0...250</td><td></td></tr><tr><td>S2</td><td>0...50</td><td>40...140</td><td></td></tr><tr><td>S3</td><td>0...250</td><td>30...480</td><td></td></tr><tr><td>S4</td><td>-15...35</td><td>0...100</td><td></td></tr><tr><td>S5</td><td>0...100</td><td>40...240</td><td></td></tr><tr><td>S6</td><td>-20...80</td><td>40...90</td><td>✓</td></tr><tr><td>S7</td><td>0...160</td><td>0...150</td><td></td></tr></table>	*del*Setting	Range [°C]	Range [°F]	Factory setting	S0	-50...50	-30...130		S1	-10...120	0...250		S2	0...50	40...140		S3	0...250	30...480		S4	-15...35	0...100		S5	0...100	40...240		S6	-20...80	40...90	✓	S7	0...160	0...150	
	*del*Setting	Range [°C]	Range [°F]	Factory setting																																		
	S0	-50...50	-30...130																																			
	S1	-10...120	0...250																																			
	S2	0...50	40...140																																			
	S3	0...250	30...480																																			
	S4	-15...35	0...100																																			
	S5	0...100	40...240																																			
	S6	-20...80	40...90	✓																																		
	S7	0...160	0...150																																			
	Accuracy temperature	±0.5°C @ 21°C [±0.9°F @ 70°F] @ measuring range setting S2 and S4																																				
	Long term stability	±0.06°C p.a. @ 21°C [±0.11°F p.a. @ 70°F]																																				
	Time constant τ (63%) in the air duct	Typical 100 s @ 0 m/s																																				
Safety data	Protection class IEC/EN	III, Protective Extra-Low Voltage (PELV)																																				
	Power source UL	Class 2 Supply																																				
	Degree of protection IEC/EN	IP65																																				

Technical data

Safety data	Degree of protection NEMA/UL	NEMA 4X
	Housing	UL Enclosure Type 4X
	EU Conformity	CE Marking
	Certification IEC/EN	IEC/EN 60730-1
	Quality Standard	ISO 9001
	UL Approval	cULus acc. to UL60730-1A/-2-9, CAN/CSA E60730-1/-2-9
	Type of action	Type 1
	Rated impulse voltage supply	0.8 kV
	Pollution degree	3
	Ambient humidity	Max. 95% RH, non-condensing
	Ambient temperature	-35...50°C [-30...120°F]
	Fluid temperature	-35...70°C [-30...160°F]
	Housing surface temperature	Max. 70°C [160°F]
Materials	Housing	Cover: PC, orange Bottom: PC, orange Seal: NBR70, black UV resistant
	Cable gland	PA6, black

Safety notes


This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application. Unauthorised modifications are prohibited. The product must not be used in relation with any equipment that in case of a failure may threaten humans, animals or assets.

Ensure all power is disconnected before installing. Do not connect to live/operating equipment.

Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.

The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Remarks

General remarks concerning sensors Sensing devices with a transducer should always be operated in the middle of the measuring range to avoid deviations at the measuring end points. The ambient temperature of transducer electronics should be kept constant. The transducers must be operated at a constant supply voltage (± 0.2 V). When switching the supply voltage on/off, onsite power surges must be avoided.

Remark: Occurring draft leads to a better carrying-off of dissipative power at the sensor. Thus temporally limited fluctuations might occur upon temperature measurement.

Remarks

Build-up of self-heating by electrical dissipative power

Temperature sensors with electronic components always have a dissipative power which affects the temperature measurement of the ambient air. The dissipation in active temperature sensors shows a linear increase with rising operating voltage. The dissipative power should be taken into account when measuring temperature.

In case of a fixed operating voltage (± 0.2 V), this is normally done by adding or reducing a constant offset value. As Belimo transducers work with a variable operating voltage, for reasons of production engineering only one operating voltage can be taken into consideration. Transducers 0...10 V / 4...20 mA have a standard setting at an operating voltage of DC 24 V. This means that at this voltage, the expected measuring error of the output signal will be the least. For other operating voltages, the offset error will be increased by a changing power loss of the sensor electronics.

If a readjustment directly at the active sensor should be necessary during later operation, this can be done with the following adjustment methods.

- For sensors with NFC or dongle with the corresponding Belimo app
- For sensors with a trimming potentiometer on the sensor board
- For bus sensors via bus interface with a corresponding software variable


Parts included

Description	Type
Mounting plate S housing	A-22D-A09
Mounting kit, with 6 mounting brackets	A-22D-A08

Accessories

Optional accessories	Description	Type
	Connection adapter flex conduit, M20x1.5, for cable gland 1x 6 mm, Multipack 10 pcs.	A-22G-A01.1
	Mounting kit, with 6 mounting brackets	A-22D-A08


Wiring diagram



The following measuring ranges can be adjusted through the jumper settings:

*del*Setting	Range [°C]	Range [°F]	Factory setting
S0	-50...50	-30...130	
S1	-10...120	0...250	
S2	0...50	40...140	
S3	0...250	30...480	
S4	-15...35	0...100	
S5	0...100	40...240	
S6	-20...80	40...90	
S7	0...160	0...150	

Dimensions



L = Probe length

Type	Probe length	Weight
22MT-144	3 m	0.24 kg
22MT-145	6 m	0.21 kg

Dimensions

Type	Probe length	Weight
22MT-148	15 m	0.21 kg

Further documentation

- Installation instructions