


Liquid differential pressure sensor

Active sensor (4...20 mA) for differential pressure measurement in HVAC systems. The sensor is suitable for liquids, refrigerants or non-aggressive gases. The housing is made of stainless steel and is IP65 / NEMA 4 rated. Optional stainless steel or brass pipe connection adapters also available.


Type Overview

Type	Measuring range [bar]	Output signal active pressure	Overpressure	Negative overpressure	Burst pressure
22WDP-131	0...1	4...20 mA	6 bar	-1 bar	21 bar
22WDP-132	0...2.5	4...20 mA	6 bar	-1 bar	21 bar
22WDP-134	0...4	4...20 mA	16 bar	-1 bar	21 bar
22WDP-135	0...6	4...20 mA	16 bar	-1 bar	21 bar

Measuring range: The sensor can measure differential pressure (dp) within this range.

The maximum operating pressure (relative pressure to atmosphere prel) can be higher. For further information, please refer to "Product features".

Technical data

Electrical data	Nominal voltage	DC 24 V
	Nominal voltage range	DC 13.5...26.4 V
	Power consumption DC	0.5 W
	Electrical connection	Connector plug for wire 0.5...1.5 mm ²
	Cable entry	Angle plug according to DIN 43650, construction A
Functional data	Medium	Water Water-glycol mixture Steam
	Current output	1x 4...20 mA, max. resistance 900 Ω
	Mechanical connection	pressure connector: G 1/4"
	Mounting	Installation location unrestricted
	Typical response time	37 ms
Measuring data	Measured values	Differential pressure
Specification Pressure	Accuracy	±1% of measuring range @ -5...75°C [23...167°F]
	Long term stability	±2.5% / 10 yr.
Safety data	Protection class IEC/EN	III, Protective Extra-Low Voltage (PELV)
	Power source UL	Class 2 Supply
	Degree of protection IEC/EN	IP65
	Degree of protection NEMA/UL	NEMA 4
	EU Conformity	CE Marking
	Certification IEC/EN	IEC/EN 60730-1
	Quality Standard	ISO 9001
	Ambient humidity	Max. 95% RH, non-condensing
	Ambient temperature	-10...50°C [14...122°F]
	Fluid temperature	-10...80°C [15...175°F]

Technical data

Safety data	Fluid temperature note	At a fluid temperature of $<2^{\circ}\text{C}$ [$<36^{\circ}\text{F}$], frost protection must be guaranteed steam inlet @ max. 100 kPa [15 psi]
Materials	Housing	Bottom: Stainless steel 1.4305 Top Cover: Die cast aluminium
	Housing seal	EPDM
	Fluid wetted parts	Stainless steel 1.4301, Ceramic
Terms	Abbreviations	dp: differential pressure between high and low pressure prel: relative pressure to ambient pressure

Safety notes



This device has been designed for use in stationary heating, ventilation and air-conditioning systems and must not be used outside the specified field of application. Unauthorised modifications are prohibited. The product must not be used in relation with any equipment that in case of a failure may threaten humans, animals or assets.

Ensure all power is disconnected before installing. Do not connect to live/operating equipment.

Only authorised specialists may carry out installation. All applicable legal or institutional installation regulations must be complied with during installation.

The device contains electrical and electronic components and must not be disposed of as household refuse. All locally valid regulations and requirements must be observed.

Product Features

Application The device is designed with an internal membrane that directly measures the differential pressure of the fluid applied to each side of the sensing element. The operating pressure prel can be higher than the measuring range dp if it is guaranteed that the differential pressure stays within the measuring range.

Differential pressure $\leq$ measuring range (dp)

Operating pressure $<$ burst pressure (prel)

Measuring range (dp)

The sensor can measure the differential pressure (dp) within this range.

Overpressure (dp)


Maximum differential pressure (dp) that the device can withstand without permanent damage. No measurement is possible within the overpressure range.

Negative overpressure (dp)

Maximum negative differential pressure (dp) that the device can withstand without permanent damage.


Burst pressure (prel)

Maximum relative pressure (prel) up to which the device housing is tight. If this pressure is exceeded, the sensor will leak or burst.




Accessories

Optional accessories	Description	Type
	Pipe connector, Brass, Pipe 6 mm to G 1/4" (external thread), Set of 2 pcs.	A-22WP-A04
	Pipe connector, Stainless steel, Pipe 6 mm to G 1/4" (external thread), Set of 2 pcs.	A-22WP-A06
	Pipe connector, Brass, Pipe 8 mm to G 1/4" (external thread), Set of 2 pcs.	A-22WP-A08
	Pipe connector, Stainless steel, Pipe 8 mm to G 1/4" (external thread), Set of 2 pcs.	A-22WP-A10
	Mounting bracket for 22WDP-..., Metal	A-22WP-A11
	Pipe connector, Brass, Pipe 6 mm to G 1/4" (external thread)	EXT-BC1414
Electrical accessories	Description	Type
	Connecting cable 1.5 m for 22WP-... / 22WDP-...	EXT-MR-249184
	Connecting cable 5 m for 22WP-... / 22WDP-...	EXT-MR-249185

Wiring diagram


Dimensions



Type	Weight
22WDP-131	0.54 kg
22WDP-132	0.54 kg
22WDP-134	0.54 kg
22WDP-135	0.54 kg

Further documentation

- Installation instructions